



120 gr. A-Tip® Match

Item No. 24568

C.O.L.: 2.400"

G1 B.C.: 0.675

G7 B.C.: 0.340

VELOCITY (FPS – feet per second)							
POWDER	2200	2300	2400	2500	2550	2600	2650
LEVEREVOLUTION	24.5 gr.	25.5 gr.	26.5 gr.	27.5 gr.	28.0 gr.	28.5 gr.	
STABALL MATCH	22.3 gr.	24.0 gr.	25.7 gr.	27.4 gr.	28.3 gr.	29.1 gr.	
VARGET	23.1 gr.	24.2 gr.	25.3 gr.	26.4 gr.	27.0 gr.		
TAC	23.4 gr.	24.3 gr.	25.2 gr.	26.1 gr.	26.6 gr.		
ALLIANT RL-15.5	23.7 gr.	24.8 gr.	25.9 gr.	27.0 gr.	27.5 gr.	28.1 gr.	
SW PRECISION	23.9 gr.	24.9 gr.	25.9 gr.	27.0 gr.			
CFE 223	23.8 gr.	25.0 gr.	26.2 gr.	27.4 gr.	28.0 gr.	28.6 gr.	29.0 gr.
VIHT N-550	24.6 gr.	25.8 gr.	26.9 gr.	28.0 gr.	28.6 gr.	29.1 gr.	
ALLIANT RL-17	25.1 gr.	26.3 gr.	27.4 gr.	28.6 gr.	29.1 gr.	29.7 gr.	30.3 gr.
SW MATCH RIFLE	23.4 gr.	24.5 gr.	25.6 gr.	26.8 gr.	27.3 gr.	27.9 gr.	
VIHT N-150	18.5 gr.	21.2 gr.	23.9 gr.	26.6 gr.			
POWER PRO 2000 MR	24.3 gr.	25.5 gr.	26.7 gr.	27.9 gr.	28.6 gr.	29.2 gr.	29.8 gr.
ACCURATE 4064	22.9 gr.	24.0 gr.	25.1 gr.	26.2 gr.			
SW THE CREED	24.0 gr.	25.2 gr.	26.4 gr.	27.6 gr.	28.2 gr.	28.8 gr.	

NOTE: This 6mm ARC reloading data is intended for use in bolt action rifles safe for pressures up to 62,000 psi. It is NOT for use in AR-15 style (gas gun) rifles.